

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) P5200 ADHESION PROMOTER - RED
Product code : 000000000002763338

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation
Address : South Saginaw Road
Midland Michigan 48686
Telephone : (989) 496-6000
Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-
ment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.

DOW CORNING(R) P5200 ADHESION PROMOTER - RED

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.
Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Inorganic and organic compounds
Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Octamethyltrisiloxane	107-51-7	>= 70 - < 90
1-Methoxyisopropyl orthosilicate	18407-95-9	>= 5 - < 10
Titanium tetrabutanolate	5593-70-4	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye damage.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Fire burns more vigorously than would be expected.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures : Remove all sources of ignition.
Use personal protective equipment.

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version 1.1	Revision Date: 10/17/2015	SDS Number: 957732-00002	Date of last issue: 02/10/2015 Date of first issue: 02/10/2015
----------------	------------------------------	-----------------------------	---

- gency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Ensure all equipment is electrically grounded before beginning transfer operations.
This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations.
Restrict flow velocity in order to reduce the accumulation of static electricity.
- Local/Total ventilation : Use with local exhaust ventilation.
Use only in an area equipped with explosion proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapors or spray mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Non-sparking tools should be used.

DOW CORNING(R) P5200 ADHESION PROMOTER - RED

Version 1.1	Revision Date: 10/17/2015	SDS Number: 957732-00002	Date of last issue: 02/10/2015 Date of first issue: 02/10/2015
----------------	------------------------------	-----------------------------	---

Keep container tightly closed.
Keep away from water.
Protect from moisture.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Octamethyltrisiloxane	107-51-7	TWA	200 ppm	DCC OEL

Hazardous components without workplace control parameters

Ingredients	CAS-No.
1-Methoxyisopropyl orthosilicate	18407-95-9
Titanium tetrabutanolate	5593-70-4

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-1-ol	71-23-8	TWA	100 ppm	ACGIH
		TWA	200 ppm 500 mg/m ³	NIOSH REL
		ST	250 ppm 625 mg/m ³	NIOSH REL
		TWA	200 ppm 500 mg/m ³	OSHA Z-1

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version 1.1 Revision Date: 10/17/2015 SDS Number: 957732-00002 Date of last issue: 02/10/2015
Date of first issue: 02/10/2015

Butan-1-ol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m ³	NIOSH REL
		TWA	100 ppm 300 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
Use only in an area equipped with explosion proof exhaust ventilation.
Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Antistatic gloves
Material : Impervious gloves
Material : Flame retardant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Hygiene measures : Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

: Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : red

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 153 °C

Flash point : 30.8 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.820

Solubility(ies)

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: 1 cSt
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Flammable liquid and vapor. Vapors may form explosive mixture with air. Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: Exposure to moisture. Handling operations that can promote accumulation of static charges. Heat, flames and sparks.
Incompatible materials	: Oxidizing agents Water
Hazardous decomposition products	
Contact with water or humid air	: Propan-1-ol Butan-1-ol
Thermal decomposition	: Formaldehyde

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:**Octamethyltrisiloxane:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on test data

Acute inhalation toxicity : LC50 (Rat): > 2350 ppm
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on test data

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on test data

1-Methoxyisopropyl orthosilicate:

Acute oral toxicity : LD50 (Rat): 1,530 mg/kg
Remarks: Based on test data

Titanium tetrabutanolate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Octamethyltrisiloxane:**

Species: Rabbit
Result: No skin irritation

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Remarks: Based on test data

1-Methoxyisopropyl orthosilicate:

Species: Rabbit
Result: No skin irritation
Remarks: Based on test data

Titanium tetrabutanolate:

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Ingredients:**Octamethyltrisiloxane:**

Result: No eye irritation
Remarks: Based on data from similar materials

1-Methoxyisopropyl orthosilicate:

Species: Rabbit
Result: No eye irritation
Remarks: Based on test data

Titanium tetrabutanolate:

Species: Rabbit
Result: Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.
Respiratory sensitization: Not classified based on available information.

Ingredients:**Octamethyltrisiloxane:**

Assessment: Does not cause skin sensitization.

Test Type: Human repeat insult patch test (HRIPT)

Species: Humans
Remarks: No known sensitising effect.
Based on test data

Titanium tetrabutanolate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Octamethyltrisiloxane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version 1.1	Revision Date: 10/17/2015	SDS Number: 957732-00002	Date of last issue: 02/10/2015 Date of first issue: 02/10/2015
----------------	------------------------------	-----------------------------	---

Result: negative
Remarks: Based on test data

: Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on test data

Titanium tetrabutanolate:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:**Octamethyltrisiloxane:**

Effects on fertility

: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat, male and female
Application Route: inhalation (vapor)
Symptoms: No effects on fertility.
Remarks: Based on test data

Test Type: Uterotrophic assay
Species: Rat, female
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on test data

Effects on fetal development

: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat, male and female
Application Route: inhalation (vapor)
Symptoms: No effects on fetal development.
Remarks: Based on test data

Reproductive toxicity - As-

: No evidence of adverse effects on sexual function and fertility,

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

assessment or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Ingredients:**Titanium tetrabutanolate:**

Assessment: May cause respiratory irritation.

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Octamethyltrisiloxane:**

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity**Ingredients:****Octamethyltrisiloxane:**

Species: Rat

Application Route: Ingestion

Remarks: Based on test data

Species: Rat

Application Route: inhalation (vapor)

Remarks: Based on test data

Aspiration toxicity

Not classified based on available information.

Further information**Ingredients:****Octamethyltrisiloxane:**

Remarks: This material contains octamethyltrisiloxane (L3). Repeated inhalation exposure in rats to L3 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Octamethyltrisiloxane:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.019 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on test data
No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.020 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.0094 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 0.027 mg/l
Method: OECD Test Guideline 210
Remarks: Based on test data
No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia sp.): > 0.15 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: No toxicity at the limit of solubility.
- Ecotoxicology Assessment
- Acute aquatic toxicity : This product has no known ecotoxicological effects.
- Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability**Ingredients:****Octamethyltrisiloxane:**

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Method: OECD Test Guideline 310
- Stability in water : Degradation half life: 329 h pH: 7
Method: OECD Test Guideline 111
Remarks: Based on test data

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Bioaccumulative potential**Ingredients:****Octamethyltrisiloxane:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)
 Bioconcentration factor (BCF): ≥ 500
 Method: OECD Test Guideline 305
 Remarks: Biomagnification factor < 1

Partition coefficient: n-octanol/water : log Pow: ≥ 4
 Remarks: Based on test data

Titanium tetrabutanolate:

Partition coefficient: n-octanol/water : log Pow: 0.88

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

Waste Code : D001: Ignitability

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not burn, or use a cutting torch on, the empty drum.
 If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (Octamethyltrisiloxane, Organo Titanate)

Class : 3

Packing group : III

Labels : 3

IATA-DGR

DOW CORNING(R) P5200 ADHESION PROMOTER - RED

Version 1.1	Revision Date: 10/17/2015	SDS Number: 957732-00002	Date of last issue: 02/10/2015 Date of first issue: 02/10/2015
----------------	------------------------------	-----------------------------	---

UN/ID No. : UN 1993
 Proper shipping name : Flammable liquid, n.o.s.
 (Octamethyltrisiloxane, Organo Titanate)
 Class : 3
 Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (Octamethyltrisiloxane, Organo Titanate)
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1993
 Proper shipping name : FLAMMABLE LIQUIDS, N.O.S.
 (Octamethyltrisiloxane, Organo Titanate)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Butan-1-ol	71-36-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Octamethyltrisiloxane	107-51-7	70 - 90 %
Tetrapropyl orthosilicate	682-01-9	5 - 10 %
1-Methoxyisopropyl orthosilicate	18407-95-9	5 - 10 %
Titanium tetrabutanolate	5593-70-4	1 - 5 %
Butan-1-ol	71-36-3	0 - 0.1 %

New Jersey Right To Know

Octamethyltrisiloxane	107-51-7	70 - 90 %
Tetrapropyl orthosilicate	682-01-9	5 - 10 %
1-Methoxyisopropyl orthosilicate	18407-95-9	5 - 10 %
Titanium tetrabutanolate	5593-70-4	1 - 5 %

California Prop. 65 This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

REACH : Consult your local Dow Corning office.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

DSL : This product contains one or more substances which are not on the Canadian Domestic Substances List (DSL). Import of this product into Canada has volume limitations. For volume limits please consult Dow Corning Regulatory Compliance.


DOW CORNING(R) P5200 ADHESION PROMOTER - RED

Version 1.1 Revision Date: 10/17/2015 SDS Number: 957732-00002 Date of last issue: 02/10/2015
 Date of first issue: 02/10/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 DCC OEL : Dow Corning Guide
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average
 DCC OEL / TWA : Time weighted average
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.
 OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Conven-

**DOW CORNING(R) P5200 ADHESION
PROMOTER - RED**

Version	Revision Date:	SDS Number:	Date of last issue: 02/10/2015
1.1	10/17/2015	957732-00002	Date of first issue: 02/10/2015

tion for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/17/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8