

ACCESSORIES

Sanding sleeves	6
Table inserts	6
Rubber sanding drums	5
Drum washers	5
Hex wrench	1

We recommend that you purchase your accessories from the same store that sold you the tool. Use good quality accessories marked with a well-known brand name. Choose the type according to the work you intend to undertake. Refer to the accessory packaging for further details. Store personnel can assist you and offer advice.

READ ALL INSTRUCTIONS BEFORE USING THIS APPLIANCE

INSTRUCTIONS PERTAINING TO A RISK OF INJURY

GENERAL

A. GROUNDING INSTRUCTIONS

- 1. All grounded, cord-connected tools:**
In the event of a malfunction or breakdown, grounding provides a path of least resistance for electric current to reduce the risk of electric shock. This tool is equipped with an electric cord having an equipment-grounding conductor and a grounding plug. The plug must be plugged into a matching outlet that is properly installed and grounded in accordance with all local codes and ordinances. Do not modify the plug provided – if it will not fit the outlet, have the proper outlet installed by a qualified electrician. Improper connection of the equipment-grounding conductor can result in a risk of electric shock. The conductor with insulation having an outer surface that is green with or without yellow stripes is the equipment-grounding conductor. If repair or replacement of the electric cord or plug is necessary, do not connect the equipment-grounding conductor to a live terminal. Check with a qualified electrician or service personnel if the grounding instructions are not completely understood, or if in doubt as to whether the tool is properly grounded. Use only 3-wire extension cords that have 3-prong grounding plugs and 3-pole

receptacles that accept the tool's plug. Repair or replace damaged or worn cord immediately.

- 2. Grounded, cord-connected tools intended for use on a supply circuit having a nominal rating less than 150V:**
This tool is intended for use on a circuit that has an outlet that looks like the one illustrated in Sketch A in Figure 1. The tool has a grounding plug that looks like the plug illustrated in Sketch A in Figure 1. A temporary adapter, which looks like the adapter illustrated in Sketches B and C, may be used to connect this plug to a 2-pole receptacle as shown in Sketch B if a properly grounded outlet is not available. The temporary adapter should be used only until a properly grounded outlet can be installed by a qualified electrician. The green-colored rigid ear, lug and the like, extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box.
 - 3. Grounded, cord-connected tools intended for use on a supply circuit having a nominal rating between 150-250V, inclusive:**
This tool is intended for use on a circuit that has an outlet that looks like the one illustrated in Sketch D in Figure 1. The tool has a grounding plug that looks like the plug illustrated in Sketch D in Figure 1. Make sure the tool is connected to an outlet having the same configuration as the plug. No adapter is available or should be used with this tool. If the tool must be reconnected for use on a different type of electric circuit, the reconnection should be made by qualified service personnel; and after reconnection, the tool should comply with all local codes and ordinances.
 - 4. Permanently connected tools:**
This tool should be connected to a grounded metal permanent wiring system; or to a system having an equipment-grounding conductor.
- B. FOR ALL DOUBLE-INSULATED TOOLS**
- 1. Replacement parts**
When servicing use only identical replacement parts.
 - 2. Polarized Plugs**
To reduce the risk of electric shock, this equipment has a polarized plug (one blade is wider than the other). This plug will fit in a